



Sigma series packaging equipment



Features

- Full colour touch screen
- Extensive production data and alarm reports
- Quick release shoulder for pack size changes
- Quick change sealing parts for easy maintenance
- Full safety guarding and interlocks
- Compatible with auger fillers, volumetric cup fillers and multi-head scales
- Wrapping materials: Polyethylene, cellophane, paper/polyethylene, aluminium/polyethylene

Technical information

- Bag width from 80 mm to 440 mm
- Bag height from 60 mm to 720 mm
- Pack weight from 10 g up to 25 kg
- Pack speeds vary between 10 and 80 BPM depending on model
- Pack formats: pillow pack, flat bottom pack

Machine specifications

Sigma model	1	2	3	5	6	Baler
Min/max bag width (mm)	80-150	80-240	80-240	80-320	150-440	150-400
Min/max bag height (mm)	60-200	60-340	60-340	60-450	200-720	200-600
Max speed (BPM)	60 (95)	45	80	80	25	10
Max pack weight	500 g	2,5 kg	2,5 kg	5 kg	10 kg	25 kg
Touch screen	n/a	Opt	Std	Std	Std	n/a
Safety guarding	Std	Std	Std	Std	Std	Std
Film alarm	Opt	Opt	Std	Std	Std	Std
Auger filling	Yes	Yes	Yes	Yes	n/a	n/a
Volumetric filling	Yes	Yes	Yes	Yes	Yes	n/a
Multihead scale	Yes	Yes	Yes	Yes	Yes	n/a
Date coder, Euro slot, Hole punch, Nitrogen flush, Tear notch, Count and cut strip packs, Film slice assist (Specifications may vary with the packaging material and product to be packed)	Opt	Opt	Opt	Opt	Opt	Opt



ENGINEERING INTELLIGENCE



LIFELONG CLIENT PARTNERSHIPS



ADDING VALUE TO YOUR PRODUCE



LOCAL SKILLS, GLOBAL FOOTPRINT

Spin-off company of

